

900MHz

WRX-002 (CCR-900)

The CCR-900 video receiver offers rock-solid frequency stability by utilizing a microprocessor controlled PPL tuning system. Use this receiver for all AM band 900MHz transmitters and enjoy trouble free operation without re-tuning or adjusting in any environment.

ADVANTAGES

- 902 – 928MHz user selectable
- Convenient signal strength indicator
- Power On/Off Switch with LED indicator
- Convenient Terminal Block connectors for various power supply input options
- One Year Limited Warranty

SPECIFICATIONS

OPERATING FREQUENCY	902MHz – 928MHz
FREQUENCY SELECTION	User Selectable
FREQUENCY STABILITY	Micro Processor Controlled PLL
ANTENNA TYPE	Omnidirectional Rubber Duck
ANTENNA CONNECTOR	TNC Female
VIDEO FORMAT	NTSC
VIDEO CONNECTOR	BNC Female @ 75 Ohms 1 Volt P-P
AUDIO CONNECTOR	RCA Female @ 600 Ohms 1 Volt P-P
TEMPERATURE RANGE	-20°F to +150°F
POWER SUPPLY INCLUDED	Terminal Block Input 6.4 – 24 VDC – Polarity Protected
CURRENT CONSUMPTION	200mA @ 6.4 VDC
DIMENSIONS	5.37" x 4.25" x 1.44"
WEIGHT	416g or 14.7 oz
FCC / IC APPROVED	YES

KIT INCLUDES

- VIDEO RECEIVER
- 12 VDC POWER SUPPLY
- RUBBER DUCK ANTENNA
- ONE YEAR LIMITED WARRANTY

