

2.4GHZ

ETX-002 (T-2445)

Ideal for short to long range transmission when running cable is not possible, economical or convenient. With four user selectable frequencies, this transmitter is perfect for applications ranging from surveillance to remote monitoring.

ADVANTAGES

- Eliminates the need for cabling or trenching
- Sends video from locations normally not possible, convenient or economical with cable
- Ideal for portable, temporary and covert surveillance or monitoring applications
- Four user selectable channels
- One Year Limited Warranty

SPECIFICATIONS

OPERATING FREQUENCY	2.4108GHz – 2.4728GHz; 4 User Selectable Channels
RADIATED POWER	50mV/m @ 3m
RANGE (LINE-OF-SIGHT)	Depends on Optional Receiver Antenna
ANTENNA TYPE	Omni Directional
VIDEO FORMAT	NTSC or PAL
VIDEO CONNECTOR	RCA Male @ 75 Ohms 1 Volt P-P
AUDIO CONNECTOR	RCA Male @ 600 Ohms 1 Volt P-P
TEMPERATURE RANGE	-30°F to +170°F
POWER SUPPLY INCLUDED	8 –14 VDC Polarity Protected
CURRENT CONSUMPTION	45mA
DIMENSIONS	1" x 2.5" x 0.5"
WEIGHT	37g or 1.3 oz
FCC / IC APPROVED	YES

KITS INCLUDE

- MINI TRANSMITTER
- 12VDC POWER SUPPLY
- AA BATTERY PACK HOLDER
- ONE YEAR LIMITED WARRANTY



4 Channels

